



## RISK ASSESSMENT – GENERATORS

HAZARD	EXISTING CONTROL MEASURES	HARM (1-5)	LIKELY HOOD (1-5)	RISK (1-5)	FURTHER CONTROLS TO REDUCE RISK	RISK ACCEPTABLE Y/N
Lifting / Dropping	Unit only to be lifted by two people. Manual handling reg's to be observed	2	4	5	None	Y
Electrocution	No items to be plugged in with power on. No cables to be unplugged with unit running	4	2	5	None	Y
Burns	Unit to be sited within barrier area. No public access to unit. Access restricted to staff members	4	2	5	None	Y
Fire	Petrol to be stored in container. Container to be stored in vehicle or locked building. Filling of generator to be done when unit is cold to the touch and switched. Filling of generator to be done using spout or funnel. <b>No Spare Petrol is supplied for Hirer 6 hours supplied. No refuelling required.</b>	4	3	5	None	Y
Petrol Blower/Generator Exhaust Fumes	Unit to be run outdoors only. Exhaust must be free from obstruction. Exhaust to be pointed away from public	4	2	5	None	Y
<b>RISK ASSESSMENT CARRIED OUT BY:</b>			<b>DATE:</b>  / /			

THE ABOVE INFORMATION IS BASED ON MAUFACTURERS CRITERIA AND EXPERIENCE FROM EXTENSIVE USE OF EQUIPMENT.